

15kV 屏蔽型前/后接头 Screen front / rear connector

屏蔽型前/后接头用于电缆分支箱、环网柜、箱变等，保证了该产品可实现多分支供电。用于 $\Phi 46/\Phi 56/91.5/M16$ 套管全密封连接，适用于8.7/15kV、12/20kV交联电缆，电缆截面 $25 \sim 500\text{mm}^2$ 。



Type: AQT3-15/630KD/□
(前接头 Front connector)

1. Screened front and rear connector are suitable for cable branch unit, Ring main unit and pad-mound transformer, etc.
2. Suitable for fully-submersible connection of size $\Phi 46/\Phi 56/91.5/M16$ bushing(meet for EN50180 and EN50181).
3. Apply to 8.7/15kV、12/20kV XLPE cable, and cable cross section is $25-500\text{mm}^2$.

产品特点

能更好处理电缆断口处的电场强度、电气性能更优。空间小，独特结构设计，安装方便，容差性更高。



Type: AHT3-15/630KD/□
(后接头 Rear connector)

Characteristics

1. It can balance the electric field intensity, high performance. small space, special structure design.
2. It's easy for installation, higher tolerance.

- 1、电缆 Cable
- 2、应力锥 Cable adaptor
- 3、接地线 Earthing wire
- 4、前接头 Front connector body
- 5、套管 Bushing
- 6、屏蔽封帽 Screen cover
- 7、非屏蔽绝缘塞 Un-screen insulating plug
- 8、双头螺栓 Bolt
- 9、铜连接杆 Copper linking rod
- 10、圆头端子 Compression lug
- 11、后接头 Rear connector body

